

Teo[®]

IP Phone 9102

The Teo 9102 is a powerful 2-line desk phone, designed for practical and affordable office communications. It offers advanced Teo UC feature access, full duplex audio speakerphone, remote provisioning, and station-level paging. The 9102 is the ideal low-cost endpoint for general office use and common areas.





The Teo 9102 features dual lines, a vibrant color display, and seamless integration with the Teo UC platform. It is specifically engineered for quality performance at an attractive price point, ideal for general office use and common areas.

FEATURES

- Two SIP lines with dedicated keys
- Color display
- Local Directory (500 entries)
- Call log (600 entries, in/out/missed)
- Blacklist call blocking
- Keyboard lock
- Message waiting indicator
- Microphone mute/unmute
- Call hold / resume
- Call waiting
- Station-level multicast paging
- Caller ID display
- Time/date display
- Call transfer (attended or blind)
- Call pickup
- Redial
- Do-Not-Disturb
- Voicemail access
- Local 3-way conference
- Hot/warm line
- 10/100 network and PC ports
- Power over Ethernet or optional local power
- Full duplex speakerphone
- Headset interface with EHS support for Plantronics headsets
- Desktop or wall mount installation

TECHNICAL SPECIFICATIONS

- Power Input: 802.3af Class 2 PoE or optional local power (5 VDC / 600mA)
- Power Consumption: 1.1 W (idle), 1.8 W (peak)
- Network Port: 10/100 BaseT Ethernet with 802.3af PoE
- PC Port: 10/100 BaseT Ethernet
- Full-duplex acoustic echo cancellation (AEC)
- Dynamic Adaptive Jitter Buffer
- Packet loss concealment
- IP Configuration: static or DHCP
- VPN: L2TP (basic unencrypted) / OpenVPN
- VLAN support
- LLDP
- QoS 802.1p/q, DSCP
- Codecs: G.711u, G.711A, G.722, G.729AB
- Protocols: SIP 2.0 over UDP/TCP/TLS, RTP/SRTP, STUN, SNTP, FTP/TFTP, HTTP/HTTPS
- FCC Part 15
- CE Certified

PHYSICAL SPECIFICATIONS

- Size: 7.7" H x 6.5" W x 2.9"D
- Weight: 1.45 lbs.
- LCD Size Diagonal: 2.4" (320 x 240)
- Operating Temperature: 32 to 104° F (0 to 40° C)
- Relative Humidity: 10–65% non-condensing

